## **OPN-CHEMIE OTTO PETRI GmbH**

*Produktion techn. Aerosole - Sprays* In der Au 14, D-57290 Neunkirchen / Germany

Phone: +49 (0) 27 35 / 77 25-0 Fax: +49 (0) 27 35 / 77 25-90

www.opn-chemie.de info@opn-chemie.de



# **Product Information**

# **OPN-Silicone Spray Type S**

- release agent
- slip agent
- lubricant

#### **Properties:**

- lubricant
- temperature resistant from about -50°C up to +250°C

### **Application areas:**

- release agent fort he plastics technology thermoplastics and duroplastics, rubber (except silicone rubber), always test suitability!
- release agent and lubricant for foam and textile processing, paper, wood, printing and packing industry
- can be used as installation aid, e.g. at hose connections
- care product for plastic surfaces etc. always test suitability

### **Application:**

Our information are recommendations based on our experience. We accept no liability for any damage without tests concerning suitability for the specific application, without preliminary trials and if the products is misused. Shake the can. Spray thinly from a distance of 20 to 30 cm. IMPORTANT: Do not use if parts should be treated afterwards (varnishing, printing, etc.)! Avoid that the substance gets on the ground - danger of slipping!

Only for professional use! Always observe safety data sheet before use.

Delivery information: Art.-No. 60300

Spray: 400 ml Content, Packing Unit: 12 Cans/Carton

Observe the information on the label and of the EC-safety data sheet!

Our technical information has been compiled carefully to the best of our knowledge. Because of the many possible influences during processing and use of the products they do not relieve the processor of its own, conscientious exams! A legally binding assurance of certain properties or of the suitability for a particular purpose can not be derived from our information. Existing laws and regulations must be checked and observed from the processor of our products before use in his own responsibility.