

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU

OPN-Silicone Spray Type S

Version number: 6.0 Date of compilation: 2015-06-12 Revision: 2023-12-07

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier 1.1

> Trade name OPN-Silicone Spray Type S

Unique formula identifier (UFI) G10D-65AW-M00J-K5RW

Other means of identification

Article number 60300

Tariff No 34039900

Relevant identified uses of the substance or mixture and uses advised against 1.2

> Relevant identified uses Industrial use

Professional use Consumer use (private households)

Sector of use Release and care products

Uses advised against Do not use for products which come into contact with foodstuffs

1.3 Details of the supplier of the safety data sheet

> **OPN-CHEMIE GmbH** In der Au 14 57290 Neunkirchen

www.opn-chemie.de

Competent person responsible for the safety data sheet Barbara Angelika Gros-Petri e-mail (competent person) baerbel.petri@opn-chemie.de

Emergency telephone number 1.4

Emergency information service Poison Information Center Freiburg +49(0)761/19240

SECTION 2: Hazards identification

Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Hazard class and category	Hazard state- ment
2.3	Aerosols	Aerosol 1	H222,H229
3.2	Skin corrosion/irritation	Skin Irrit. 2	H315
3.8D	Specific target organ toxicity - single exposure (narcotic effects, drowsiness)	STOT SE 3	H336
4.1C	Hazardous to the aquatic environment - chronic hazard	Aquatic Chronic 3	H412

Remarks

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

Spillage and fire water can cause pollution of watercourses.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

Signal word

Danger

Pictograms GHS02, GHS07



Page 1 / 12 (en)

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU

OPN-Silicone Spray Type S

Version number: 6.0 Date of compilation: 2015-06-12 Revision: 2023-12-07

Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P271 Use only outdoors or in a well-ventilated area.
P312 Call a POISON CENTER/doctor if you feel unwell.
P332+P313 If skin irritation occurs: Get medical advice/attention.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.
P501 Dispose of contents / container in accordance with national regulations of the disposal.

Additional labelling requirements

Buildup of explosive mixtures possible without sufficient ventilation.

Hazardous ingredients for labelling

Hydrocarbons, C5-C7 n-alkanes, isoalkanes, <5% n-hexane

2.3 Other hazards

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0.1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture).

3.2 Mixtures

Description of the mixture

Mixture of substances listed below with nonhazardous additions

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
Butane	CAS No 106-97-8 EC No 203-448-7 REACH Reg. No 01-2119474691- 32-xxxx	50 – < 75	Flam. Gas 1A / H220 Press. Gas L / H280	
Propane	CAS No 74-98-6 EC No 200-827-9 REACH Reg. No 01-2119486944- 21-xxxx	10 - < 25	Flam. Gas 1A / H220 Press. Gas C / H280	
Pentane	CAS No 109-66-0 EC No 203-692-4 REACH Reg. No 01-2119459286- 30-xxxx	5 - < 10	Flam. Liq. 2 / H225 STOT SE 3 / H336 Asp. Tox. 1 / H304 Aquatic Chronic 2 / H411	

(en) Page 2 / 12

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU

OPN-Silicone Spray Type S

Version number: 6.0 Date of compilation: 2015-06-12 Revision: 2023-12-07

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
Hydrocarbons, C6, isoalkanes, <5% n-hexane	EC No 931-254-9 REACH Reg. No 01-2119484651- 34-xxxx	1 - < 5	Flam. Liq. 2 / H225 Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304 Aquatic Chronic 2 / H411	
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	EC No 926-605-8 REACH Reg. No 01-2119486291- 36-xxxx	1 - < 5	Flam. Liq. 2 / H225 STOT SE 3 / H336 Asp. Tox. 1 / H304 Aquatic Chronic 2 / H411	
Isobutane	CAS No 75-28-5 EC No 200-857-2 REACH Reg. No 01-2119485395- 27-xxxx	1 - < 5	Flam. Gas 1A / H220 Press. Gas C / H280	
Cyclohexane	CAS No 110-82-7 EC No 203-806-2 REACH Reg. No 01-2119463273- 41-xxxx	0 - < 0.25	Flam. Liq. 2 / H225 Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304 Aquatic Acute 1 / H400 Aquatic Chronic 1 / H410	

3.3 Remarks

For full text of abbreviations: see SECTION 16

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take offi mmediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Narcotic effects.

4.3 Indication of any immediate medical attention and special treatment needed none

(en) Page 3 / 12

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU

OPN-Silicone Spray Type S

Version number: 6.0 Date of compilation: 2015-06-12 Revision: 2023-12-07

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray. BC-powder.

Unsuitable extinguishing media

Water jet.

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture.

Hazardous combustion products

Carbon monoxide (CO). Carbon dioxide (CO2).

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

Storage class (LGK)

2 B

· Flammability hazards

Do not spray on an open flame or other ignition source. Protect from sunlight.

Consideration of other advice

· Packaging compatibilities

Only packagings which are approved (e.g. acc. to ADR) may be used.

7.3 Specific end use(s)

No further relevant information available.

(en) Page 4 / 12

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU

OPN-Silicone Spray Type S

Version number: 6.0 Date of compilation: 2015-06-12 Revision: 2023-12-07

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

this information is not available

Relevant DNELs/DMELs/PNECs and other threshold levels

Relevant DNELs of components of the mixture

Relevant DNELs of components

	F					
Name of sub- stance	CAS No	End- point	Threshol d level	Protection goal, route of exposure	Used in	Exposure time
Pentane	109-66-0	DNEL	3,000 mg/ m ³	Human, inhalatory	Worker (industry)	Chronic - systemic effects
Pentane	109-66-0	DNEL	432 mg/kg bw/day	Human, dermal	Worker (industry)	Chronic - systemic effects
Hydrocarbons, C6, isoalkanes, <5% n- hexane		DNEL	5,306 mg/ m ³	Human, inhalatory	Worker (industry)	Chronic - systemic effects
Hydrocarbons, C6, isoalkanes, <5% n- hexane		DNEL	13,964 mg/ kg bw/day	Human, dermal	Worker (industry)	Chronic - systemic effects
Hydrocarbons, C6- C7, isoalkanes, cyc- lics, <5% n-hexane		DNEL	13,964 mg/ kg	Human, dermal	Worker (industry)	Chronic - systemic effects
Hydrocarbons, C6- C7, isoalkanes, cyc- lics, <5% n-hexane		DNEL	5,306 mg/ m ³	Human, inhalatory	Worker (industry)	Chronic - systemic effects
Cyclohexane	110-82-7	DNEL	700 mg/m ³	Human, inhalatory	Worker (industry)	Chronic - systemic effects
Cyclohexane	110-82-7	DNEL	700 mg/m ³	Human, inhalatory	Worker (industry)	Acute - systemic effects
Cyclohexane	110-82-7	DNEL	700 mg/m ³	Human, inhalatory	Worker (industry)	Chronic - local ef- fects
Cyclohexane	110-82-7	DNEL	700 mg/m ³	Human, inhalatory	Worker (industry)	Acute - local effects
Cyclohexane	110-82-7	DNEL	2,016 mg/ kg bw/day	Human, dermal	Worker (industry)	Chronic - systemic effects

Relevant PNECs of components of the mixture

Relevant PNECs of components

Name of sub- stance	CAS No	End- point	Threshol d level	Organism	Environmental compartment	Exposure time
Pentane	109-66-0	PNEC	3,600 ^{µg/} l	Microorganisms	Sewage treatment plant (STP)	Short-term (single instance)
Pentane	109-66-0	PNEC	1.2 ^{mg/kg}	Benthic organisms	Sediments	Short-term (single instance)
Pentane	109-66-0	PNEC	1.2 ^{mg/kg}	Pelagic organisms	Sediments	Short-term (single instance)
Pentane	109-66-0	PNEC	880 ^{µg/} l	Aquatic organisms	Water	Intermittent release
Pentane	109-66-0	PNEC	230 ^{µg/} l	Aquatic organisms	Freshwater	Short-term (single instance)

(en) Page 5 / 12

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU

OPN-Silicone Spray Type S

Version number: 6.0 Date of compilation: 2015-06-12 Revision: 2023-12-07

Relevant PNECs	of components
nelevani fineos	S OF COHIDOHERIES

Title County Title County Coun						
Name of sub- stance	CAS No	End- point	Threshol d level	Organism	Environmental compartment	Exposure time
Pentane	109-66-0	PNEC	230 ^{µg/} l	Aquatic organisms	Marine water	Short-term (single instance)
Pentane	109-66-0	PNEC	3,600 ^{µg/} l	Aquatic organisms	Sewage treatment plant (STP)	Short-term (single instance)
Pentane	109-66-0	PNEC	1.2 ^{mg/} kg	Aquatic organisms	Freshwater sedi- ment	Short-term (single instance)
Pentane	109-66-0	PNEC	1.2 ^{mg/kg}	Aquatic organisms	Marine sediment	Short-term (single instance)
Pentane	109-66-0	PNEC	0.55 ^{mg/} kg	Terrestrial organ- isms	Soil	Short-term (single instance)
Cyclohexane	110-82-7	PNEC	0.207 ^{mg/} l	Aquatic organisms	Freshwater	Short-term (single instance)
Cyclohexane	110-82-7	PNEC	0.207 ^{mg/} l	Aquatic organisms	Marine water	Short-term (single instance)
Cyclohexane	110-82-7	PNEC	3.24 ^{mg/} l	Aquatic organisms	Sewage treatment plant (STP)	Short-term (single instance)
Cyclohexane	110-82-7	PNEC	3.627 ^{mg/} kg	Aquatic organisms	Freshwater sedi- ment	Short-term (single instance)
Cyclohexane	110-82-7	PNEC	3.627 ^{mg/} kg	Aquatic organisms	Marine sediment	Short-term (single instance)
Cyclohexane	110-82-7	PNEC	2.99 ^{mg/} kg	Terrestrial organ- isms	Soil	Short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Do not spray in eyes. If required use tight-fitting goggles.

Skin protection

Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374.

Type of material

NBR: acrylonitrile-butadiene rubber.

Material thickness

> 0,7 mm

Breakthrough times of the glove material

>480 minutes (permeation: level 6)

Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

Operate if possible out of doors or in a well-ventilated place. In case of inadequate ventilation wear respiratory protection. Type: A-P2 (combined filters against particles and organic gases and vapours, colour code: Brown/White).

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

(en) Page 6 / 12

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU

OPN-Silicone Spray Type S

Version number: 6.0 Date of compilation: 2015-06-12 Revision: 2023-12-07

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Aerosol (Spray aerosol)
Colour Colourless
Odour Characteristic

Initial boiling point and boiling range

Not applicable, as aerosol.*

Flammability (solid, gas) flammable aerosol in accordance with GHS criteria

Explosive limits 1 vol% - 15 vol%

Flash point Not applicable, as aerosol.*

Water solubility Insoluble

Vapour pressure 4 bar at 20 °C

7 bar at 50 °C

Density 0.61 g/ml at 20 °C

9.2 Other information

Other safety characteristics

* The finished mixture in an aerosol container is formed after addition of propellant. Several details are not measurable in an hermetic closed, pressurized container.

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Do not spray on an open flame or other ignition source. Keep away from heat.

Hints to prevent fire or explosion

Protect from sunlight.

Physical stresses which might result in a hazardous situation and have to be avoided

High temperatures.

10.5 Incompatible materials

Oxidisers.

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Shall not be classified as acutely toxic.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

(en) Page 7 / 12

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU

OPN-Silicone Spray Type S

Version number: 6.0 Date of compilation: 2015-06-12 Revision: 2023-12-07

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

• Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

• Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

11.2 Information on other hazards

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life with long lasting effects.

Ordinance on systems for handling water-polluting substances (Ordinance on facilities for handling substances hazardous to water) (AwSV): WGK (Germany) 2, obviously hazardous to water

12.2 Persistence and degradability

Degradability of components

Name of sub- stance	CAS No	Process	Degradation rate	Time	Method	Source
Pentane	109-66-0	Oxygen deple- tion	3 %	7 d		ECHA
Hydrocarbons, C6, isoalkanes, <5% n-hexane		Oxygen deple- tion	83 %	10 d		ECHA
Hydrocarbons, C6-C7, isoalkanes, cyc- lics, <5% n-hex- ane		Oxygen deple- tion	83 %	10 d		

12.3 Bioaccumulative potential

Bioaccumulative potential of components

Name of substance	CAS No	BCF	Log KOW	BOD5/COD	
Butane	106-97-8		1.09 (pH value: 7, 20 °C)		
Propane	74-98-6		1.09 (pH value: 7, 20 °C)		
Pentane	109-66-0	171	3.45 (pH value: 7, 25 °C)		
Hydrocarbons, C6, isoalkanes, <5% n-hexane		501.2	3.6 (pH value: 7, 20 °C)		
Isobutane	75-28-5		1.09 (pH value: 7, 20 °C)		
Cyclohexane	110-82-7	167	3.44 (pH value: 7, 25 °C)		

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance in a concentration of ≥ 0,1%.

(en) Page 8 / 12

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU

OPN-Silicone Spray Type S

Version number: 6.0 Date of compilation: 2015-06-12 Revision: 2023-12-07

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0.1\%$.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Relevant provisions relating to waste

List of wastes

15 01 04 Metallic packaging 15 01 10 Packaging containing residues of or contaminated by dangerous substances 16 05 04 Containing hazardous gases in pressure containers (including halons)

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1	UN number or ID number	r

ADR/RID/ADN 1950 IMDG-Code UN 1950 ICAO-TI UN 1950

14.2 UN proper shipping name

ADR/RID/ADN **AEROSOLS** IMDG-Code **AFROSOLS** ICAO-TI Aerosols, flammable

14.3 Transport hazard class(es)

ADR/RID/ADN 2 (2.1) IMDG-Code 2.1 ICAO-TI 2.1

14.4 Packing group Not assigned

14.5 Environmental hazards Non-environmentally hazardous acc. to the dangerous goods regu-

Special precautions for user 14.6

Provisions for dangerous goods (ADR) should be complied within the premises.

14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN)Additional information

Classification code 5F Danger label(s) 2.1



Special provisions (SP) 190, 327, 344, 625

Excepted quantities (EQ) FΩ Limited quantities (LQ) 1 L Transport category (TC) 2 Tunnel restriction code (TRC) D

Page 9 / 12 (en)

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU

OPN-Silicone Spray Type S

Version number: 6.0 Date of compilation: 2015-06-12 Revision: 2023-12-07

International Maritime Dangerous Goods Code (IMDG)Additional information

Marine pollutant -

Danger label(s) 2.1



Special provisions (SP) 63, 190, 277, 327, 344, 381, 959

Excepted quantities (EQ) E0
Limited quantities (LQ) 1 L
EmS F-D, S-U
Stowage category -

International Civil Aviation Organization (ICAO-IATA/DGR)Additional information Danger label(s) 2.1



Special provisions (SP)

Excepted quantities (EQ)

Limited quantities (LQ)

A145, A167

E0

30 kg

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant provisions of the European Union (EU) Restrictions according to REACH, Annex XVII

none of the ingredients are listed

List of substances subject to authorisation (REACH, Annex XIV)/SVHC - candidate list

none of the ingredients are listed

Directive 75/324/EEC relating to aerosol dispensers

Classification of the gas/aerosol Extremely flammable

Labelling Keep out of reach of children. Pressurized container: may burst if heated. Keep away

from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures

exceeding 50°C / 122°F.

Additional information

Industrial Emissions Directive (IED)

VOC content 93.7 %

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

none of the ingredients are listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

none of the ingredients are listed Water Framework Directive (WFD) none of the ingredients are listed

Regulation on persistent organic pollutants (POP)

none of the ingredients are listed National regulations (Germany)

Ordinance on systems for handling water-polluting substances (Ordinance on facilities for handling substances hazardous

to water)(AwSV)

Water hazard class 2 (obviously hazardous to water)

Technical instructions on air quality control (Germany)

Number	Group of substances	Class	Conc.	Mass flow	Mass con- centration	Notation
5.2.5	Organic substances		≥ 25 wt%	0.5 ^{kg/} h	50 ^{mg/} m³	3)

Notation

3) A total mass flow of 0.50 kg/h or a total mass concentration of 50 mg/m³, each of which to be indicated as total carbon, shall not be exceeded (except organic particulate matter)

Storage of hazardous substances in non-stationary containers (TRGS 510) (Germany)

Storage class (LGK) 2 B (Aerosol dispensers and lighters)

(en) Page 10 / 12

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU

OPN-Silicone Spray Type S

Version number: 6.0 Date of compilation: 2015-06-12 Revision: 2023-12-07

National inventories

Country	Inventory	Status
EU	REACH Reg.	Not all ingredients are listed

Legend

REACH Reg. REACH registered substances

15.2 Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

16.1 Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.3		Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0,1\%$.	Yes

16.2 Abbreviations and acronyms

ADN Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures

(European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways).

ADR Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the Interna-

tional Carriage of Dangerous Goods by Road).

ADR/RID/ADN Agreements concerning the International Carriage of Dangerous Goods by Road/Rail/Inland Waterways (ADR/RID/

AĎN)

Aquatic Acute Hazardous to the aquatic environment - acute hazard. Aquatic Chronic Hazardous to the aquatic environment - chronic hazard.

Asp. Tox. Aspiration hazard.
BCF Bioconcentration factor.
BOD Biochemical Oxygen Demand.

CAS Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances).

CLP Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures.

COD Chemical oxygen demand.

DGR Dangerous Goods Regulations (see IATA/DGR).

DMEL Derived Minimal Effect Level.

DNEL Derived No-Effect Level.

EC No The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of

substances commercially available within the EU (European Union).

ED Endocrine disruptor.

EINECS European Inventory of Existing Commercial Chemical Substances.

ELINCS European List of Notified Chemical Substances.

EmS Emergency Schedule.
Flam. Gas Flammable gas.
Flam. Liq. Flammable liquid.

GHS "Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations.

IATA International Air Transport Association.

IATA/DGR Dangerous Goods Regulations (DGR) for the air transport (IATA).

ICAO International Civil Aviation Organization.
ICAO-TI Technical instructions for the safe transp

ICAO-TI Technical instructions for the safe transport of dangerous goods by air.

IMDG International Maritime Dangerous Goods Code. IMDG-Code International Maritime Dangerous Goods Code.

LGK Lagerklasse (storage class according to TRGS 510, Germany).

Log KOW n-Octanol/water.
NLP No-Longer Polymer.

PBT Persistent, Bioaccumulative and Toxic.
PNEC Predicted No-Effect Concentration.

Press. Gas Gas under pressure.

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals.

RID Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning

the International carriage of Dangerous goods by Rail).

Skin Corr. Corrosive to skin. Skin Irritant to skin.

STOT SE Specific target organ toxicity - single exposure.

SVHC Substance of Very High Concern.

TRGS Technische Regeln für Gefahrstoffe (technical rules for hazardous substances, Germany).

VOC Volatile Organic Compounds.

VPvB Very Persistent and very Bioaccumulative.

(en) Page 11 / 12

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU

OPN-Silicone Spray Type S

Version number: 6.0 Date of compilation: 2015-06-12 Revision: 2023-12-07

Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures.

Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN).

International Maritime Dangerous Goods Code (IMDG).

Dangerous Goods Regulations (DGR) for the air transport (IATA).

16.4 Classification procedure

Physical and chemical properties. The classification is based on tested mixture.

Health hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

16.5 List of relevant phrases (code and full text as stated in section 2 and 3)

Extremely flammable gas. Extremely flammable aerosol.
Highly flammable liquid and vapour. H222 H225 Pressurised container: May burst if heated. H229 Contains gas under pressure; may explode if heated. H280 May be fatal if swallowed and enters airways. H304 H315 Causes skin irritation. H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects.

Toxic to aquatic life with long lasting effects. H410 H411 H412 Harmful to aquatic life with long lasting effects.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

Page 12 / 12 (en)