

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.05.2017




Version number 17

Revision: 05.04.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** OPN-Spray Grease with PTFE
- **Article number:** 61425
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Relevant identified uses** industrial use, professional use
- **Application of the substance / the mixture** Lubricant
- **Uses advised against:**
consumer use (private households)
Do not use for products that are intended for contact with food - exclude food contact.
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
OPN-CHEMIE OTTO PETRI GMBH
In der Au 14
D-57290 Neunkirchen/Germany
Tel.: +49 (0) 2735 / 7725-0 Fax: +49 (0) 2735 / 7725-90
E-Mail: info@opn-chemie.de Web: www.opn-chemie.de
- **Further information obtainable from:**
Safety data sheets Mrs. Barbara Angelika Gros-Petri
Tel.: +49 (0) 2735 / 7725-20 E-Mail: baerbel.petri@opn-chemie.de
- **1.4 24 hours Emergency telephone number:**
Vergiftungs-Informations-Zentrale Freiburg +49 (0) 761 / 192 40

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
-  GHS02 flame
Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
-  GHS09 environment
Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.
-  GHS07
Skin Irrit. 2 H315 Causes skin irritation.
STOT SE 3 H336 May cause drowsiness or dizziness.
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS07 GHS09

- **Signal word** Danger
- **Hazard-determining components of labelling:**
Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cycloalkanes, < 5 % n-hexane

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.05.2017

Version number 17

Revision: 05.04.2017

Trade name: OPN-Spray Grease with PTFE

(Contd. of page 1)

· Hazard statements

- H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
 H315 Causes skin irritation.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P260 Do not breathe vapours/spray.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P312 Call a POISON CENTER/doctor if you feel unwell.
 P391 Collect spillage.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 P501 Dispose of contents/container to hazardous or special waste collection point.

· Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

· 2.3 Other hazards
· Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

EC number: 927-510-4 Reg.nr.: 01-2119475515-33-xxxx	Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	20-<25%
EC number: 921-024-6 Reg.nr.: 01-2119475514-35-xxxx	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cycloalkanes, < 5 % n-hexane ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	20-<25%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane ⚠ Flam. Gas 1, H220; Press. Gas C, H280	10-<20%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane ⚠ Flam. Gas 1, H220; Press. Gas C, H280	5-<10%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane ⚠ Flam. Gas 1, H220; Press. Gas C, H280	1.0-<2.5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

GB

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.05.2017

Version number 17

Revision: 05.04.2017

Trade name: OPN-Spray Grease with PTFE

(Contd. of page 2)

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:**
Supply fresh air; consult doctor in case of complaints.
Take affected persons into fresh air and keep quiet.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
Immediately remove any clothing soiled by the product.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**
Breathing difficulty
Headache
Dizziness
Dizziness
Coughing
Nausea
- **4.3 Indication of any immediate medical attention and special treatment needed**
If swallowed or in case of vomiting, danger of entering the lungs.
Later observation for pneumonia and pulmonary oedema.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
Foam
Fire-extinguishing powder
Carbon dioxide
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
Can form explosive gas-air mixtures.
Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.
- **Additional information**
Cool endangered receptacles with water spray.
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.05.2017

Version number 17

Revision: 05.04.2017

Trade name: OPN-Spray Grease with PTFE

(Contd. of page 3)

- **6.4 Reference to other sections** See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Avoid contact with skin and eyes.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **Ingredients with limit values that require monitoring at the workplace:**

CAS: 106-97-8 butane

WEL	Short-term value: 1810 mg/m ³ , 750 ppm
	Long-term value: 1450 mg/m ³ , 600 ppm
	Carc (if more than 0.1% of buta-1.3-diene)

- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.
- **Respiratory protection:** Use suitable respiratory protective device in case of insufficient ventilation.
- **Recommended filter device for short term use:** Filter AX
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Material of gloves**
Nitrile rubber, NBR
Recommended thickness of the material: ≥ 0.45 mm
- **Penetration time of glove material**
 ≥ 240 min
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.05.2017

Version number 17

Revision: 05.04.2017

Trade name: OPN-Spray Grease with PTFE

(Contd. of page 4)

· **Eye protection:**

Tightly sealed goggles

· **Body protection:** Protective work clothing

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**· **General Information**· **Appearance:**

· Form:	Aerosol
· Colour:	Whitish
· Odour:	Petrol-like

· **Change in condition**

· Melting point/freezing point:	Undetermined.
· Initial boiling point and boiling range:	< 0 °C

· **Flash point:** Not applicable, as aerosol.· **Ignition temperature:** >200 °C· **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.· **Density at 20 °C:** 0.70071 g/cm³· **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

· **Viscosity:**

· Dynamic:	Not determined.
· Kinematic:	Not determined.
· Organic solvents:	71.0 %
· VOC (EC)	497.5 g/l

· **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.· **10.2 Chemical stability**· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.· **10.3 Possibility of hazardous reactions** No dangerous reactions known.· **10.4 Conditions to avoid** No further relevant information available.· **10.5 Incompatible materials:** No further relevant information available.· **10.6 Hazardous decomposition products:**Aldehyde
Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

· **11.1 Information on toxicological effects**· **Acute toxicity** Based on available data, the classification criteria are not met.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.05.2017

Version number 17

Revision: 05.04.2017

Trade name: OPN-Spray Grease with PTFE

(Contd. of page 5)

· LD/LC50 values relevant for classification:
ATE (Acute Toxicity Estimates)

Inhalative	LC50/4 h	243 mg/l (rat)
------------	----------	----------------

Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes

Oral	LD50	>5840 mg/kg (rat)
------	------	-------------------

Dermal	LD50	>2920 mg/kg (rat)
--------	------	-------------------

Inhalative	LC50/4 h	>23.3 mg/l (rat)
------------	----------	------------------

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cycloalkanes, < 5 % n-hexane

Oral	LD50	>5840 mg/kg (rat)
------	------	-------------------

Dermal	LD50	>2920 mg/kg (rat)
--------	------	-------------------

Inhalative	LC50/4 h	<25.2 mg/l (rat)
------------	----------	------------------

CAS: 75-28-5 isobutane

Inhalative	LC50/4 h	>50 mg/l (rat)
------------	----------	----------------

CAS: 74-98-6 propane

Inhalative	LC50/4 h	20 mg/l (rat)
------------	----------	---------------

CAS: 106-97-8 butane

Inhalative	LC50/4 h	658 mg/l (rat)
------------	----------	----------------

· Primary irritant effect:
· Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation Based on available data, the classification criteria are not met.

· Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

· CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
· Germ cell mutagenicity Based on available data, the classification criteria are not met.

· Carcinogenicity Based on available data, the classification criteria are not met.

· Reproductive toxicity Based on available data, the classification criteria are not met.

· STOT-single exposure

May cause drowsiness or dizziness.

· STOT-repeated exposure Based on available data, the classification criteria are not met.

· Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

· 12.1 Toxicity
· Aquatic toxicity:
Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes

EC50/48 h	3 mg/l (daphnia)
-----------	------------------

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cycloalkanes, < 5 % n-hexane

EC50/48 h	3 mg/l (daphnia)
-----------	------------------

· 12.2 Persistence and degradability No further relevant information available.

· 12.3 Bioaccumulative potential No further relevant information available.

· 12.4 Mobility in soil No further relevant information available.

· Ecotoxicological effects:
· Remark: Toxic for fish

· Additional ecological information:
· General notes:

Also poisonous for fish and plankton in water bodies.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.05.2017

Version number 17

Revision: 05.04.2017

Trade name: OPN-Spray Grease with PTFE

(Contd. of page 6)

Toxic for aquatic organisms
 Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
 Do not allow product to reach ground water, water course or sewage system.
 Danger to drinking water if even small quantities leak into the ground.

12.5 Results of PBT and vPvB assessment

 · **PBT:** Not applicable.

 · **vPvB:** Not applicable.

 · **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

 · **13.1 Waste treatment methods**

 · **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

 · **European waste catalogue**

16 05 04*	gases in pressure containers (including halons) containing hazardous substances
15 01 04	metallic packaging

 · **Uncleaned packaging:**

 · **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

 · **14.1 UN-Number**

 · **ADR,RID,ADN, IMDG, IATA** UN1950

 · **14.2 UN proper shipping name**

 · **ADR/RID/ADN** UN1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS
 · **IMDG** AEROSOLS, MARINE POLLUTANT
 · **IATA** AEROSOLS, flammable

 · **14.3 Transport hazard class(es)**

 · **ADR/RID/ADN**

 · **Class** 2 5F Gases.
 · **Label** 2.1

 · **IMDG**

 · **Class** 2.1
 · **Label** 2.1

 · **IATA**

 · **Class** 2.1

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.05.2017

Version number 17

Revision: 05.04.2017

Trade name: OPN-Spray Grease with PTFE

(Contd. of page 7)

· Label	2.1
· 14.4 Packing group · ADR,RID,ADN, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR/RID/ADN):	Product contains environmentally hazardous substances: Solvent Naphta Yes Symbol (fish and tree) Symbol (fish and tree)
· 14.6 Special precautions for user · Danger code (Kemler): · EMS Number: · Stowage Code · Segregation Code	Warning: Gases. - F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR/RID/ADN · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
· Transport category · Tunnel restriction code	2 D
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category
P3a FLAMMABLE AEROSOLS
E2 Hazardous to the Aquatic Environment
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

(Contd. on page 9)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.05.2017

Version number 17

Revision: 05.04.2017

Trade name: OPN-Spray Grease with PTFE

(Contd. of page 8)

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

· **Abbreviations and acronyms:**

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ICAO: International Civil Aviation Organisation
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Gas 1: Flammable gases – Category 1
- Aerosol 1: Aerosols – Category 1
- Press. Gas C: Gases under pressure – Compressed gas
- Flam. Liq. 2: Flammable liquids – Category 2
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- Asp. Tox. 1: Aspiration hazard – Category 1
- Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

· *** Data compared to the previous version altered.**