

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 09.12.2019



Version number 31

Revision: 28.11.2019

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** OPN-Long Term Primer RUST STOP grey
- **Article number:** 66420
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Relevant identified uses** industrial use, professional use
- **Application of the substance / the mixture** Anticorrosion additive
- **Uses advised against:**  
consumer use (private households)  
Do not use for products that are intended for contact with food - exclude food contact.
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
OPN-CHEMIE OTTO PETRI GMBH  
In der Au 14  
D-57290 Neunkirchen/Germany  
Tel.: +49 (0) 2735 / 7725-0 Fax: +49 (0) 2735 / 7725-90  
E-Mail: info@opn-chemie.de Web: www.opn-chemie.de
- **Further information obtainable from:**  
Safety data sheets Mrs. Barbara Angelika Gros-Petri  
Tel.: +49 (0) 2735 / 7725-20 E-Mail: baerbel.petri@opn-chemie.de
- **1.4 24 hours Emergency telephone number:**  
Vergiftungs-Informations-Zentrale Freiburg +49 (0) 761 / 192 40

### SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
- |   |  |
|---|--|
|  | GHS02 flame  |
| Aerosol 1   | H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. |
- |   |   |
|---|---|
|  | GHS07   |
| Eye Irrit. 2  | H319 Causes serious eye irritation.                     |
| STOT SE 3   | H336 May cause drowsiness or dizziness.                 |
| Asp. Tox. 1   | H304 May be fatal if swallowed and enters airways.      |
| Aquatic Chronic 3   | H412 Harmful to aquatic life with long lasting effects. |

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



- **Signal word** Danger
- **Hazard-determining components of labelling:**  
xylene  
acetone  
Hydrocarbons C9-C11, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics  
Hydrocarbons, C9, aromatics

(Contd. on page 2)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 09.12.2019

Version number 31

Revision: 28.11.2019

**Trade name: OPN-Long Term Primer RUST STOP grey**

(Contd. of page 1)

**· Hazard statements**

- H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.  
 H319 Causes serious eye irritation.  
 H336 May cause drowsiness or dizziness.  
 H412 Harmful to aquatic life with long lasting effects.

**· Precautionary statements**

- P101 If medical advice is needed, have product container or label at hand.  
 P102 Keep out of reach of children.  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P211 Do not spray on an open flame or other ignition source.  
 P251 Do not pierce or burn, even after use.  
 P26 ' R Q R W E U H D W K H Y D S R X U V V S U D \\  
 P271 Use only outdoors or in a well-ventilated area.  
 P280 : H D U S U R W H F W L Y H J O R Y H V S U R W H F W L Y H F O R W K L Q J H \ H S U R  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P410+P412 3 U R W H F W I U R P V X Q O L J K W ' R Q R W H [ S R V H W R W H P S H U D W X U

P501 ' L V S R V H R I F R Q W H Q W V F R Q W D L Q H U L Q D F F R U G D Q F H Z L W K

**· Additional information:**

- EUH066 Repeated exposure may cause skin dryness or cracking.  
 Buildup of explosive mixtures possible without sufficient ventilation.

**· 2.3 Other hazards**
**· Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

**· 3.2 Mixtures**

- **Description:** Mixture of substances listed below with nonhazardous additions.

**· Dangerous components:**

|   |  |         |
|---|--|---------|
| CAS: 67-64-1<br>EINECS: 200-662-2<br>Reg.nr.: 01-2119471330-49-xxxx   | acetone<br>⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336   | 25-<50% |
| CAS: 74-98-6<br>EINECS: 200-827-9<br>Reg.nr.: 01-2119486944-21-xxxx   | propane<br>⚠ Flam. Gas 1, H220; Press. Gas (Comp.), H280   | 10-<20% |
| CAS: 106-97-8<br>EINECS: 203-448-7<br>Reg.nr.: 01-2119474691-32-xxxx  | butane<br>⚠ Flam. Gas 1, H220; Press. Gas (Comp.), H280  | 10-<20% |
| CAS: 1330-20-7<br>EINECS: 215-535-7<br>Reg.nr.: 01-2119488216-32-xxxx | xylene<br>⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 | 5-<10%  |
| CAS: 75-28-5<br>EINECS: 200-857-2<br>Reg.nr.: 01-2119485395-27-xxxx   | isobutane<br>⚠ Flam. Gas 1, H220; Press. Gas (Comp.), H280   | 5-<10%  |
| EC number: 919-857-5<br>Reg.nr.: 01-2119463258-33-xxxx                | Hydrocarbons C9-C11, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics<br>⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ STOT SE 3, H336            | 5-<10%  |

(Contd. on page 3)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 09.12.2019

Version number 31

Revision: 28.11.2019

**Trade name: OPN-Long Term Primer RUST STOP grey**

(Contd. of page 2)

EC number: 918-668-5

Reg.nr.: 01-2119455851-35-xxxx

Hydrocarbons, C9, aromatics

 Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic  
 Chronic 2, H411; STOT SE 3, H335-H336

2.5-&lt;5%

 · **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

#### · 4.1 Description of first aid measures

##### · After inhalation:

Supply fresh air; consult doctor in case of complaints.

Take affected persons into fresh air and keep quiet.

##### · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Immediately remove any clothing soiled by the product.

##### · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

##### · After swallowing: Do not induce vomiting; call for medical help immediately.

#### · 4.2 Most important symptoms and effects, both acute and delayed

Breathing difficulty

Headache

Dizziness

Dizziness

Nausea

#### · 4.3 Indication of any immediate medical attention and special treatment needed

If swallowed or in case of vomiting, danger of entering the lungs.

Later observation for pneumonia and pulmonary oedema.

### SECTION 5: Firefighting measures

#### · 5.1 Extinguishing media

##### · Suitable extinguishing agents:

Fire-extinguishing powder

Carbon dioxide

Use fire extinguishing methods suitable to surrounding conditions.

Foam

##### · 5.2 Special hazards arising from the substance or mixture

 Can form explosive gas-air mixtures.

##### · 5.3 Advice for firefighters

##### · Protective equipment:

 Wear self-contained respiratory protective device.

##### · Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

### SECTION 6: Accidental release measures

#### · 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

#### · 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

#### · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 4)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 09.12.2019

Version number 31

Revision: 28.11.2019

**Trade name: OPN-Long Term Primer RUST STOP grey**

(Contd. of page 3)

- Dispose contaminated material as waste according to item 13.
- Ensure adequate ventilation.
- **6.4 Reference to other sections**
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
- Ensure good ventilation/exhaustion at the workplace.
- Avoid contact with skin and eyes.
- **Information about fire - and explosion protection:**
- Keep ignition sources away - Do not smoke.
- Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
- Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **Ingredients with limit values that require monitoring at the workplace:**

**CAS: 67-64-1 acetone**

|     |  |
|-----|--|
| WEL | Short-term value: 3620 mg/m <sup>3</sup> , 1500 ppm<br>Long-term value: 1210 mg/m <sup>3</sup> , 500 ppm |
|-----|--|

**CAS: 106-97-8 butane**

|     |   |
|-----|---|
| WEL | Short-term value: 1810 mg/m <sup>3</sup> , 750 ppm<br>Long-term value: 1450 mg/m <sup>3</sup> , 600 ppm<br>Carc (if more than 0.1% of buta-1.3-diene) |
|-----|---|

**CAS: 1330-20-7 xylene**

|     |  |
|-----|--|
| WEL | Short-term value: 441 mg/m <sup>3</sup> , 100 ppm<br>Long-term value: 220 mg/m <sup>3</sup> , 50 ppm<br>Sk, BMGV |
|-----|--|

- **Ingredients with biological limit values:**

**CAS: 1330-20-7 xylene**

|      |  |
|------|--|
| BMGV | 650 mmol/mol creatinine<br>Medium: urine<br>Sampling time: post shift<br>Parameter: methyl hippuric acid |
|------|--|

- **Additional information:** The lists valid during the making were used as basis.

- **8.2 Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.

(Contd. on page 5)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 09.12.2019

Version number 31

Revision: 28.11.2019

**Trade name: OPN-Long Term Primer RUST STOP grey**

(Contd. of page 4)

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Not necessary if room is well-ventilated.

- **Recommended filter device for short term use:** Filter AX

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Material of gloves**

Butyl rubber, BR

Recommended thickness of the material:  $\geq 0.7$  mm

- **Penetration time of glove material**

$\geq 60$  min

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**

Safety glasses



Tightly sealed goggles

- **Body protection:** Protective work clothing

### SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

**Form:** Aerosol  
**Colour:** According to product specification

- **Odour:** Acetone-like

- **Odour threshold:** Not determined.

- **pH-value:** Not determined.

- **Change in condition**

**Melting point/freezing point:** Undetermined.

**Initial boiling point and boiling range:**  $< 0$  °C

- **Flash point:** Not applicable, as aerosol.

- **Flammability (solid, gas):** Not applicable.

- **Ignition temperature:**  $> 200$  °C

- **Decomposition temperature:** Not determined.

- **Auto-ignition temperature:** Not determined.

- **Explosive properties:** Not determined.

- **Explosion limits:**

**Lower:** Not determined.

**Upper:** Not determined.

(Contd. on page 6)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 09.12.2019

Version number 31

Revision: 28.11.2019

Trade name: OPN-Long Term Primer RUST STOP grey

(Contd. of page 5)

|  |  |
|--|--|
| · <b>Vapour pressure:</b>                        | Not determined.                            |
| · <b>Density at 20 °C:</b>                       | 0.78657 g/cm <sup>3</sup>                  |
| · <b>Relative density</b>                        | Not determined.                            |
| · <b>Vapour density</b>                          | Not determined.                            |
| · <b>Evaporation rate</b>                        | Not applicable.                            |
| · <b>Solubility in / Miscibility with water:</b> | Not miscible or difficult to mix.          |
| · <b>Partition coefficient: n-octanol/water:</b> | Not determined.                            |
| · <b>Viscosity:</b>                              |  |
| <b>Dynamic:</b>                                  | Not determined.                            |
| <b>Kinematic:</b>                                | Not determined.                            |
| <b>Organic solvents:</b>                         | 75.1 %                                     |
| <b>VOC (EC)</b>                                  | 590.8 g/l                                  |
| <b>Solids content:</b>                           | 0.0 %                                      |
| · <b>9.2 Other information</b>                   | No further relevant information available. |

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

#### · LD/LC50 values relevant for classification:

##### ATE (Acute Toxicity Estimates)

|            |          |              |
|------------|----------|--------------|
| Dermal     | LD50     | 14,050 mg/kg |
| Inhalative | LC50/4 h | 141 mg/l     |

##### CAS: 67-64-1 acetone

|            |          |                       |
|------------|----------|-----------------------|
| Oral       | LD50     | 5,800 mg/kg (rat)     |
| Dermal     | LD50     | 20,000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | ~76 mg/l (rat)        |

##### CAS: 74-98-6 propane

|            |          |                |
|------------|----------|----------------|
| Inhalative | LC50/4 h | >20 mg/l (rat) |
|------------|----------|----------------|

##### CAS: 106-97-8 butane

|            |          |                |
|------------|----------|----------------|
| Inhalative | LC50/4 h | 658 mg/l (rat) |
|------------|----------|----------------|

##### CAS: 1330-20-7 xylene

|            |          |                   |
|------------|----------|-------------------|
| Dermal     | LD50     | 1,100 mg/kg (ATE) |
| Inhalative | LC50/4 h | 11 mg/l (ATE)     |

##### CAS: 75-28-5 isobutane

|            |          |                |
|------------|----------|----------------|
| Inhalative | LC50/4 h | 658 mg/l (rat) |
|------------|----------|----------------|

(Contd. on page 7)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 09.12.2019

Version number 31

Revision: 28.11.2019

**Trade name: OPN-Long Term Primer RUST STOP grey**

(Contd. of page 6)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**  
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard**  
May be fatal if swallowed and enters airways.

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Harmful to aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **European waste catalogue**

|           |   |
|-----------|---|
| 16 05 04* | gases in pressure containers (including halons) containing hazardous substances |
| 15 01 04  | metallic packaging  |

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR/RID/ADN, IMDG, IATA** UN1950
- **14.2 UN proper shipping name**
- **ADR/RID/ADN** UN1950 AEROSOLS

(Contd. on page 8)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.12.2019

Version number 31

Revision: 28.11.2019

Trade name: OPN-Long Term Primer RUST STOP grey

(Contd. of page 7)

|  |  |
|--|--|
| <ul style="list-style-type: none"> <li>· IMDG</li> <li>· IATA</li> </ul> | <p>AEROSOLS</p> <p>AEROSOLS, flammable</p> |
|--|--|

- 14.3 Transport hazard class(es)
- ADR/RID/ADN



|  |                               |
|--|-------------------------------|
| <ul style="list-style-type: none"> <li>· Class</li> <li>· Label</li> </ul> | <p>2 5F Gases.</p> <p>2.1</p> |
|--|-------------------------------|

- IMDG, IATA



|  |                       |
|--|-----------------------|
| <ul style="list-style-type: none"> <li>· Class</li> <li>· Label</li> </ul> | <p>2.1</p> <p>2.1</p> |
|--|-----------------------|

|   |             |
|---|-------------|
| <ul style="list-style-type: none"> <li>· 14.4 Packing group</li> <li>· ADR/RID/ADN, IMDG, IATA</li> </ul> | <p>Void</p> |
|---|-------------|

|  |           |
|--|-----------|
| <ul style="list-style-type: none"> <li>· 14.5 Environmental hazards:</li> <li>· Marine pollutant:</li> </ul> | <p>No</p> |
|--|-----------|

|   |  |
|---|--|
| <ul style="list-style-type: none"> <li>· 14.6 Special precautions for user</li> <li>· Danger code (Kemler):</li> <li>· EMS Number:</li> <li>· Stowage Code</li> <br/> <li>· Segregation Code</li> </ul> | <p>Warning: Gases.</p> <p>-</p> <p>F-D,S-U</p> <p>SW1 Protected from sources of heat.</p> <p>SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.</p> <p>SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.</p> |
|---|--|

|   |                        |
|---|------------------------|
| <ul style="list-style-type: none"> <li>· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</li> </ul> | <p>Not applicable.</p> |
|---|------------------------|

- Transport/Additional information:

|   |   |
|---|---|
| <ul style="list-style-type: none"> <li>· ADR/RID/ADN</li> <li>· Limited quantities (LQ)</li> <li>· Excepted quantities (EQ)</li> <br/> <li>· Transport category</li> <li>· Tunnel restriction code</li> </ul> | <p>1L</p> <p>Code: E0</p> <p>Not permitted as Excepted Quantity</p> <p>2</p> <p>D</p> |
|---|---|

|   |   |
|---|---|
| <ul style="list-style-type: none"> <li>· IMDG</li> <li>· Limited quantities (LQ)</li> <li>· Excepted quantities (EQ)</li> </ul> | <p>1L</p> <p>Code: E0</p> <p>Not permitted as Excepted Quantity</p> |
|---|---|

(Contd. on page 9)



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 09.12.2019

Version number 31

Revision: 28.11.2019

**Trade name: OPN-Long Term Primer RUST STOP grey**

(Contd. of page 8)

· UN "Model Regulation": UN 1950 AEROSOLS, 2.1

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P3a** FLAMMABLE AEROSOLS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.

#### · Abbreviations and acronyms:

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ICAO: International Civil Aviation Organisation
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Gas 1: Flammable gases – Category 1
- Aerosol 1: Aerosols – Category 1
- Press. Gas (Comp.): Gases under pressure – Compressed gas
- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

(Contd. on page 10)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 09.12.2019

Version number 31

Revision: 28.11.2019

**Trade name: OPN-Long Term Primer RUST STOP grey**

(Contd. of page 9)

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· **\* Data compared to the previous version altered.**

GB