

OPN-CHEMIE OTTO PETRI GmbH

Produktion techn. Aerosole - Sprays

In der Au 14, D-57290 Neunkirchen / Germany

Phone: +49 (0) 27 35 / 77 25-0 Fax: +49 (0) 27 35 / 77 25-90

www.opn-chemie.de info@opn-chemie.de



Product Information

OPN-Signing Spray

fast, clean processing

"Day-glow colors" or "neon colors":

Art.-No. 63690 - red-orange, Art.-No. 63691 - orange, Art.-No. 63692 - yellow-orange, Art.-No. 63693 -yellow, Art.-No. 63694 - red, Art.-No. 63695 - green, Art.-No. 63696 - blue, Art.-No. 63697 - purple, Art.-No. 63698 - pink

„Normal colors“:

Art.-No. 63700 - yellow, Art.-No. 63701 - black, Art.-No. 63702 - brown, Art.-No. 63703 - orange, Art.-No. 63704 - blue, Art.-No. 63705 - green, Art.-No. 63706 - white, Art.-No. 63707 - red, Art.-No. 63708 – light blue,

„Extinguishing spray“ Art.-No. 63710

- To remove, which means to cover, invalid or incorrect labels on cardboard boxes and other packagings - **Color:** beige

Properties:

- low-odor special color for durable and long-lasting signing
- high opacity and drying in just about 2 - 3 minutes - therefore can be processed quickly and time-saving
- lightfast, water and weatherproof, durable

Application Range:

- developed for fast and clean signing
- apply shipping addresses and other labels with and without stencil
- ideal for all signing and labeling works, e.g. on cardboard boxes, wooden boxes, cardboard, paper, metal, aluminum, copper, stainless steel parts, stone, asphalt, masonry, etc.
- on request, a special writing nozzle for "hands-free labeling", is available against charge

Application:

Read processing instructions completely before starting work.

Our information are recommendations based on our experience. We accept no liability for any damage without tests concerning suitability for the specific application, without preliminary trials and if the products is misused.

Before use test for suitability and spray test. When used, the can should be at "room temperature". **Shake strongly before use and after each spray break until the stirring ball moves freely.** The area to be sprayed has to be dry, clean and free of grease. Cover surfaces that are not to be sprayed and apply targeted from approx. 15 - 20 cm.

After use, hold the can upside down and spray the valve clean until only propellant gas escapes.

Resistance: The signing color is not gasoline resistant.

Only for professional use! Always observe safety data sheet before use.

Delivery information: Art.-No. see above

Spray: 400 ml Content, Packing Unit: 12 Cans/Carton

Observe the information on the label and of the EC-safety data sheet!

Our technical information has been compiled carefully to the best of our knowledge. Because of the many possible influences during processing and use of the products they do not relieve the processor of its own, conscientious exams! A legally binding assurance of certain properties or of the suitability for a particular purpose can not be derived from our information. Existing laws and regulations must be checked and observed from the processor of our products before use in his own responsibility.

All text passages are subject to the copyright of OPN-CHEMIE OTTO PETRI GmbH.